

# MODEL SP537DC

## STANDARD CONSTRUCTION


- Material: Extruded Aluminum 6063-T6
- Frame: 5" (127 mm) deep, .063" (1.6 mm) nominal wall thickness
- Blades: 5" (127 mm) deep, .063" (1.6 mm) nominal wall thickness
- Blade Spacing: 1.875" (47.6 mm) on center
- Screen: 1/2" x .063" flattened expanded bird screen and/or 18 x 14 mesh charcoal insect screen.

## OPTIONAL ACCESSORIES


- Extended Sill Flashing
- Insulated and Non-insulated Blank-off Panels
- Flanged & Glazing Frames of various sizes
- Hinged Access Panels
- Visible Mullions
- Invisible Mullions for continuous blade appearance

## FINISHES

- 2 coat Fluoropolymer: Kynar® 500 / custom colors available in 70% PVDF (AAMA 2605). Living Building Challenge (LBC) Red List Free.
- 3 coat Fluoropolymer: Kynar 500 / Hylar 5000 custom colors available in 70% PVDF (AAMA 2605). LBC Red List Free.
- Anodic finishes: Class I and Class II in Clear, Light/Medium/Dark Bronze, Champagne, and Black.
- Prime coat
- Mill



Vertical Section



Invisible Vertical Mullion



Plan View



IMPACT RESISTANT LOUVER  
Enhanced Protection

See www.AMCA.org for all certified or listed products

This label does not signify AMCA airflow performance certification.



Qty.	Size:		M.O. <input type="checkbox"/>	Mullion Type	No. of Sections	Notes
	Actual <input type="checkbox"/>	Width				
<input type="checkbox"/>	Sill flashing:			Project:		
<input type="checkbox"/>	Screen:			Location:		
<input type="checkbox"/>	Finish:			Architect:		
	Color:			Representative:		
<input type="checkbox"/>	Other:			Date:	Job #:	



# MODEL SP537DC

## SUGGESTED SPECIFICATIONS

**General:** Furnish and install where indicated on drawings 5" (127mm) Storm Performance Louver Model SP537DC as manufactured by Industrial Louvers, Inc., Delano, MN.

**Material:** Extruded aluminum frames and blades shall be one piece 6063-T6 alloy, designed to collect and drain water to the exterior at the sill by means of integral gutters in the blades and jamb frames. Frame shall have a material thickness of .081" (2.1mm). Fixed blades shall have a material thickness of .063" (1.6mm). Frames and blades shall be joined by stainless steel mechanical fastener, and frame will be caulked to prevent water penetration to interior wall construction.

## Performance

- Free area (4' x 4' louver) = 7.65 sq. ft. 47.8%
- Free area velocity at point of beginning water penetration (.01 oz/sq. ft.) >1250 fpm
- Pressure drop @ 786 FPM velocity = .15" water
- Air volume @ 786 FPM free area velocity = 6012 CFM

**Structural Performance Testing:** The model SP537DC has been tested in accordance with and passes the following test protocols:


AMCA 540: Missile Impact Test: Enhanced Protection Missile Level E

TAS-201: Large Missile Impact Test: Louver must prevent penetration of large missile simulating airborne debris during a hurricane.

TAS-202: Uniform Static Air Pressure Test: The louver is tested to withstand a constant windload.

TAS-203: Cycle Wind Pressure Test: Tests the louvers ability to withstand both positive and negative windloads as experienced during hurricane winds.

## Air Performance Chart




The AMCA Certified Ratings Seal applies to Air Capacities in the intake model only  
Data corrected to standard air density  
Tested to AMCA 500-L, Figure 5.5

## Free Area

Square Feet (Square Meters)						
Free Area AMCA Licensed for openings up to 72" x 120"						
For free area data for larger openings, contact factory.						
3048.0	0.43	0.92	1.41	1.90	2.40	2.89
<b>120</b>	<b>4.62</b>	<b>9.91</b>	<b>15.19</b>	<b>20.47</b>	<b>25.76</b>	<b>31.04</b>
2743.2	0.39	0.83	1.27	1.72	2.16	2.6
<b>108</b>	<b>4.17</b>	<b>8.93</b>	<b>13.70</b>	<b>18.46</b>	<b>23.23</b>	<b>27.99</b>
2438.4	.034	0.73	1.12	1.51	1.89	2.28
<b>96</b>	<b>3.66</b>	<b>7.84</b>	<b>12.01</b>	<b>16.19</b>	<b>20.37</b>	<b>24.55</b>
2133.6	0.29	0.63	0.96	1.29	1.63	1.96
<b>84</b>	<b>3.14</b>	<b>6.74</b>	<b>10.33</b>	<b>13.92</b>	<b>17.52</b>	<b>21.11</b>
1828.8	0.25	0.54	0.82	1.11	1.39	1.68
<b>72</b>	<b>2.69</b>	<b>5.77</b>	<b>8.84</b>	<b>11.91</b>	<b>14.99</b>	<b>18.06</b>
1524	0.20	0.43	0.67	0.90	1.13	1.36
<b>60</b>	<b>2.18</b>	<b>4.67</b>	<b>7.15</b>	<b>9.64</b>	<b>12.13</b>	<b>14.62</b>
1219.2	0.16	0.34	0.53	0.71	0.89	1.08
<b>48</b>	<b>1.72</b>	<b>3.69</b>	<b>5.66</b>	<b>7.65</b>	<b>9.60</b>	<b>11.57</b>
914.4	0.11	0.24	0.37	0.50	0.63	0.76
<b>36</b>	<b>1.21</b>	<b>2.60</b>	<b>3.98</b>	<b>5.36</b>	<b>6.75</b>	<b>8.13</b>
609.6	0.07	0.15	0.23	0.31	0.39	0.47
<b>24</b>	<b>0.75</b>	<b>1.61</b>	<b>2.47</b>	<b>3.33</b>	<b>4.19</b>	<b>5.05</b>
304.8	0.02	0.05	0.08	0.11	0.14	0.17
<b>12</b>	<b>0.27</b>	<b>0.57</b>	<b>0.87</b>	<b>1.18</b>	<b>1.48</b>	<b>1.79</b>
<b>H/W</b>	304.8	609.6	914.4	1219	1524	1829
	<b>12</b>	<b>24</b>	<b>36</b>	<b>48</b>	<b>60</b>	<b>72</b>

## Water Penetration Chart



## Wind Driven Rain Chart

Ventilation Air Velocity (m/s)	Rainfall rate of 3" per hour (76 mm) and a wind velocity of 29 mph (47 kph).			Rainfall rate of 8" per hour (76 mm) and a wind velocity of 50 mph (47 kph).		
	Core Velocity (fpm)	Rating Effectiveness	Class	Core Velocity (fpm)	Rating Effectiveness	Class
0.0		100.0%	A		100.0%	A
0.5		100.0%	A		100.0%	A
1.0		100.0%	A		100.0%	A
1.5		100.0%	A	299	99.7%	A
2.0		100.0%	A	400	99.6%	A
2.5	499	99.9	A	492	99.5%	A
3.0	590	99.6	A	597	98.9%	B
3.5	702	99.5	A	687	97.8%	B
<b>Effectiveness Rating</b>	<b>A = 1 to 0.99</b>		<b>B = 0.989 to 0.95</b>	<b>C = 0.949 to 0.080</b>		<b>D = 0.80 to 0</b>



Industrial Louvers, Inc. certifies that Model SP537DC shown hereon is licensed to bear the AMCA Seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 511 and comply with the requirements of the AMCA Certified Ratings Program. The AMCA Certified Ratings Seal applies to air performance ratings, water penetration ratings, and wind driven rain. Hytar® and Kynar® are registered trademark of Solvay Solexix, Inc. © 2015 Industrial Louvers. All rights reserved.

CATALOG NO. SP537DC

Rev: OCT 2017



www.industriallouvers.com  
info@industriallouvers.com

511 South 7th Street, Delano MN 55328  
Tel: +1.763.972.2981 • Fax: +1.763.972.2911